

# Performance Ratings

Updated: 8/2014

Window Type	Series	Test		Structural Class	Air Infiltration	Water * Test (PSF)	Min					Max				
		size	bs/vs				Width		Height		bs/vs	Width		Height		bs/vs
Half Vent	6110 6130 6130J 6170	6050	-	LC-PG25	0.05	3.75	2	0	1	0	-	6	0	5	0	-
Half Vent		net 60 x 60	-	LC-PG30	0.03	4.5	2	0	1	0	-	5	0	5	0	-
Double Vent		10060	36	R-PG-15	0.1	3	4	0	1	0	12	10	0	6	0	36
Double Vent		9050	36	HS-LC-25	0.1	3.75	4	0	1	0	12	9	0	5	0	36
Half Vent Below / Above		-	-	HS-R-20	-		2	0	2	0		6	0	6	0	
Double Vent Above		8060	48 / 24	HS-R-20	0.08	3	4	0	2	0		8	0	6	0	48 / 24
Double Vent Below		8060	48 / 24	HS-R-20	0.08	3	4	0	2	0		8	0	6	0	48 / 24
Single Hung	6210 6230 6230J 6270	net 48 x 78	C	H-LC-30	0.06	4.5	1	0	2	6	12	4	0	6	6	
Single Hung		net 44 x 75	C	H-LC30	0.1	4.5	1	0	2	6	12	3	8	6	3	
Single Hung		net 36 x 84	36	H-LC-35	0.02	5.25	1	0	2	6	12	3	0	7	0	
Double Single Hung		net 72 x 72	C	H-LC-30	0.1	4.5	2	0	2	6	12	6	0	6	0	
Triple Single Hung		net 90 x 72	C	R-PG30	0.11	4.5	3	0	2	6	12	7	6	6	0	
Triple Single Hung		net 108 x 60	C	R-PG30	0.11	4.5	3	0	2	6	12	9	0	5	0	
Triple Single Hung		net 108 x 75	C	R-PG20	0.11	3	3	0	2	6	12	9	0	6	3	
Picture Window	6310 6331	6060	-	FW-HC-40	0.04	6	1	0	1	0	-	6	0	6	0	-
Picture Window	6331J	net 79 x 79	-	CW PG40	0.11	6	1	0	1	0	-	6	7	6	7	-
Picture Window	6340 6330	8060	-	FW-HC-40	0.01	12	1	0	1	0	-	8	0	6	0	-
Picture Window	6330J	net 79 x 79	-	CW-PG-40	0.01	15	1	0	1	0	-	6	7	6	7	-
Picture Window	6350 6360	6060	-	FW-C-35	0.01	12	1	0	1	0	-	6	0	6	0	-
Awning	6410 6430	net 48 x 36	-	AP-C-45	0.01	9	-	-	-	-	-	4	0	3	0	-
Full Awning stacked 2 vertically	6430J 6470	4060	-	AW-C-40	0.03	9	-	-	-	-	-	4	0	6	0	-
Full Casement	6510 6530 6530J 6570	net 36 x 60	-	C-C-40	0.05	7.5	-	-	-	-	-	3	0	5	0	-
Full Casement		3060	-	C-C-30	0.01	7.5	-	-	-	-	-	3	0	6	0	-
Single Casement		6060	36	C-LC-30	0.01	9	-	-	-	-	-	6	0	6	0	36
Double Casement w/ center PW		net 143 x 60	36	C-LC-25	0.08	7.5	-	-	-	-	-	11	11	5	0	36

SGD OX / XO	6610 6630	8080	-	R-PG-15	0.12	4.5	5	0	6	8	-	8	0	8	0	-
SGD OX / XO		80610	-	R-PG-20	0.06	4.5	5	0	6	8	-	8	0	6	10	-
SGD O/OX / O/XO		6090	26	SD-LC-35	0.02	5.25	6	0	6	8	-	6	0	9	0	26
Picture (Transom) Window	6610TR 6630TR	8060	-	CW-PG-35	0.01	5.25	1	6	1	6	-	8	0	6	0	-

\* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.